

Digium® Phones

Designed for Asterisk® and Switchvox®



D50

Digium's mid-level phone with 4 line keys and 10 rapid dial/busy lamp field keys for your most important contacts.

D70

Digium's executive-level phone with 6 line keys designed for administrators and executives who need to manage up to 100 contacts.

Digium phones are designed exclusively for use with Asterisk and Switchvox. Digium phones are designed exclusively for use with Asterisk and Switchvox. All models include unprecedented HDVoice and plug-and-play deployment at a price that fits any budget. Enhance your user's productivity with built-in advanced applications such as voicemail, call log, contacts, phone status, user presence, parking and queue metrics. Digium phones provide simple, intuitive access to a wealth of information, saving valuable time. With the phones' open JavaScript API, you can also build customized applications to tailor the user experience to your specific needs. Digium's highly-integrated phones are the only phones that allow you take full advantage of the flexibility and customization of Asterisk and Switchvox.



D40/D45

Digium's entry-level phone with 2 line keys. This is Digium's best value phone designed for any employee in the company.

	D40/D45 Entry-level	D50 Mid-level	D70 Executive-level
Line Keys	2	4	6
Feature Keys	4	6	10
Rapid Dial/ Busy Lamp Field Keys	0	10 keys	10 keys - 100 contacts
Ethernet LAN and PC Port	10/100Base-T (D40) 10/100/1000Base-T (D45)	10/100Base-T	10/100/1000Base-T
Main Display	3.5 inch	3.5 inch	4.5 inch
Power over Ethernet (PoE)	■	■	■
Advanced Phone Applications	■	■	■

HDVoice

Learn more at www.digium.com/phones

Digium Phones for Switchvox and Asterisk

General Specifications



D40/D45

User Interface

3.5 inch, 240 x 120 pixel backlit grayscale LCD display
2 line appearance keys
4 feature keys
4 context sensitive soft keys
6-key navigation controller
Headset, speaker, and mute keys
2-color LED Message Waiting indicator
Volume control

Connections

RJ-9 handset jack
RJ-9 headset jack
2 switched 10/100 Mbps Ethernet ports (D40)
2 switched 10/100/1000 Mbps Ethernet ports (D45)
5 volt DC power port

D50

User Interface

3.5 inch, 240 x 120 pixel backlit grayscale LCD display
4 line appearance keys
6 feature keys
4 context sensitive soft keys
6-key navigation controller
10 programmable Rapid Dial / BLF keys
Headset, speaker, and mute keys
2-color LED Message Waiting indicator
Volume control

Connections

RJ-9 handset jack
RJ-9 headset jack
2 switched 10/100 Mbps Ethernet ports
5 volt DC power port

D70

User Interface

4.5 inch, 320 by 160 pixel backlit grayscale LCD display
6 line appearance keys
10 feature keys
4 context sensitive soft keys
113 x 357 pixel backlit Rapid Dial panel LCD
10 x 10 programmable Rapid Dial / BLF keys
6-key navigation controller
Headset, speaker, and mute keys
2-color LED Message Waiting indicator
Volume control

Connections

RJ-9 handset jack
RJ-9 headset jack
2 switched 10/100/1000 Mbps Ethernet ports
5 volt DC power port

Phone Applications

Visual Voicemail
Contacts
Presence/Status
Call Log
Parked Calls
Call Queues
Info

Phone Features

Auto answer
Headset answer
Distinctive ring
Custom ring tones
Call waiting
Call transfer (blind and assisted)
Call forward
Call hold
Call parking
Call pickup
Intercom / Paging
Message Waiting Indication (MWI)
Busy Lamp Field (BLF)
3-way conferencing
Do Not Disturb (DND)
Redial
Call timer
Caller ID display

Audio Features

Handset, speaker and headset modes
HD speaker
Full duplex speakerphone with echo cancellation
Hearing aid compatible
Wideband: G.722 HD codec
Narrowband: G.711, G.726, G.729A
Acoustic Echo Cancellation (AEC)
Background noise suppression

Network Support

Static or DHCP IP address assignment
SNTP time synchronization
Priority queuing, VLAN, LLDP
NAT traversal
QoS

Language Support

English
German
French
Italian
Portuguese
Spanish
Dutch

SIP / VoIP Support

SIP v2
UDP, TCP transport
DTMF, RFC2833
SIP peer-to-peer
SIP presence (Subscribe/Notify)
Per-account digit map/dial plan
Dial using SIP URI
Dial using SIP server
Secure SIP authentication

Provisioning

DPMA (Digium Phone Module for Asterisk)
Manual provisioning from phone GUI
Auto-provisioning by DHCP option 66
Provisioning via phone UI

Management

Digest authenticated login to phone web UI
Firmware update via browser
Factory restore via GUI
Remote logging via Syslog

Regulatory Compliance

FCC Part 15 Class B
CE Mark
UL 60950

Maximum Power Consumption:

D40: 3W
D45: 5W
D50: 4W
D70: 8W

Operating Conditions

Temperature: +32° to 122° F / 0 to 50° C
Relative Humidity: 5% to 95% noncondensing

Storage Temperature

-4 to +160°F / -20 to +70°C

Size

D40/D45: 6.5 x 8.25 x 6.25 inches /
16.51 x 20.95 x 15.88 cm
D50: 6.5 x 10.5 x 6.25 inches /
16.51 x 26.67 x 15.88 cm
D70: 6.75 x 12.5 x 6.25 inches /
7.15 x 31.75 x 15.88 cm

Weight

D40/D45: 3 lbs 2 oz / 1.42 kg
D50: 3 lbs 7 oz / 1.56 kg
D70: 4 lbs / 1.81 kg

Warranty

One year

Digium, Inc. • www.digium.com

445 Jan Davis Drive NW
Huntsville, AL 35806, USA
+1 256-428-6000

Europe/Africa

South Africa +27 87 550 2590
United Kingdom +44 845 564 1419

Asia Pacific

Australia +61 28 073 4490
New Zealand +64 9 9 51 5875