



Model # KX-UT113-B

Panasonic Basic SIP Phone

- HD Voice and PoE Enabled
- Certified for Use with Broadsoft Broadworks and Digium® Asterisk®
- Environmentally Friendly - Power Consumption 1W in ECO Mode
- Two-year Limited Warranty
- LCD Display: Monochrome Graphical
- LCD Size: 242 x 55 pixels - 3 lines
- LCD Contrast: 6 levels
- LCD Backlight: None
- **INSTALL OPTIONS:**
- Desk mount tilt: No
- Wall mount: KX-A432-B (optional)
- Power adaptor: KX-A239 (optional)
- **NETWORKING:**
- Ethernet Ports: 1 - 10/100
- Power over Ethernet (PoE): Yes (Class 2)
- Bluetooth: No
- **AUDIO FEATURES:**
- Audio Codec: G.711, G.722, G.726, G.729a
- Handset, Speaker, Headset Volume: 8 levels (includes echo cancellation and distortion prevention) 15 levels
- Ringtones: 27
- Ringer Volume: 6 levels + Off
- Headset Port: 2.5 mm
- Electronic Hook: None
- Hearing Aid: Compatible with Hearing Aid TIA-801
- **KEYS:**
- Keys (total): 28
- FF Keys: -
- Navigator and Cancel Key: Yes
- **SOFTWARE FEATURES:**
- Phone Book (Entries): 30 incoming calls + 30 outgoing calls
- Call Log Entries: None
- Conferencing: 3 parties (within terminal - multi-party dependent on server)
- **IP FEATURES:**
- SIP Accounts: 2
- SIP Compatibility: RFC 3261 Standard SIP Server, Asterisk, Broadsoft
- IP Version: IPv4
- DHCP Client: Yes
- DNS: Yes
- HTTP / HTTPS: Yes

- SNTP Client: Yes
- VLAN (802.1q): Yes
- QoS (DiffServ): Yes
- **CONFIGURATION:**
- Plug & Play Configuration: Server based configuration, TR-069, BroadSoft Device Management Server
- Manual Configuration: Internal web Configurator, Local (LCD based) network configuration